

# **Because Privacy Matters**









# **Kubebooth Technical Data Sheet - Kteam**



# **Extendable**



88" Inside - W: 80" - D: 72" - H: 80"

# Weight

1800 lbs/816 kg

10mm clear tempered Ceramic painted borders Door - H: 88" x W: 36" Rear Panel - H: 88" x W: 44" Front Side Panel - H: 88" x W: 26"

# Easy to Install

NIC rating of 36 dB certified Noise cancellation technology

#### Air Exchange

Acoustics

100 complete air changes per hour

Moveable

# **Data Center**

**UL** approved 1 USB port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

# Plug & Play

# **Mobility Kit**

Includes casters with fasteners

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

# Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

# **Power Cord**

100" cord 120V/15Amp

### Wall Construction

Galvanized steel frames Sound insulation in all cavities

### **Finishes**

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted D-shape desk - W:23" x D:23"

# Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal Solution dyed polypropylene 28 oz, 10 gauge GreenGuard certified GLP8472 <450 NBS smoke

## Floor Ceiling

Substructure-rated MDF on unitized steel base.

# **Reversible Door**

Fully interchangeable left or right opening

# Worktop

White laminate wood worktop D Shape L: 45" x W: 24" Installed at an optimum height of 28"


# Felt

Interior sound absorption panels 60% recyclable

## **Options**

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit

Smart lock Occupancy lights



\*Air Flow Diagram







