





ISO 14001:2015 CERTIFIED COMPANY







Kubebooth Technical Data Sheet - Kme





Overall - W: 88" - D: 37" - H: 88" Inside - W: 80" - D: 36" - H: 80"

Weight 1200 lbs/544 kg

Glass 10mm clear tempered

Ceramic painted borders Door - H: 88" x W: 36" Rear Panel - H: 88" x W: 44" Front Side Panels - H: 88" x W: 26"

Moveable

Acoustics

NIC rating of 36 dB certified Noise cancellation technology

Air Exchange

100 complete air changes per hour

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

Plug & Play

Mobility Kit

Includes casters with fasteners

Light

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord

10ft cord 120V/15Amp



Galvanized steel frames Sound insulation in all cavities

Finishes

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions)

Aluminum hardware painted

Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal

Solution dyed polypropylene 28 oz, 10

GreenGuard certified GLP8472 <450 NBS smoke

Reversible Door

Fully interchangeable left or right opening

Floor Ceiling

Substructure-rated MDF on unitized steel


Felt

Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Occupancy lights

Height Adjustable Table



*Air Flow Diagram







