






ISO 14001:2015 CERTIFIED COMPANY





Kubebooth Technical Data Sheet - KSelfi





Easy to Install

Size Overall - W: 44" - D: 37" - H:88" Inside - W: 36" - D: 36" - H: 80"

Weight

800 lbs/362 kg

10mm clear tempered Ceramic painted borders

Door - H: 88" x W: 32" Rear Panel - H: 88" x W: 44" Front Side Panel - H: 88" x W: 12"

Moveable

Acoustics

NIC rating of 36 dB certified Noise cancellation technology

Air Exchange

100 air exchanges per hour

Data Center

UL approved

1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

Plug & Play

Mobility Kit

Includes casters with fasteners

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord 10ft cord 120V/15Amp

Wall Construction

Galvanized steel frames Sound insulation in all cavities

Finishes

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal Solution dyed polypropylene 28 oz, 10 GreenGuard certified GLP8472 < 450 NBS smoke

Floor Ceiling

Substructure rated MDF on unitized steel base

Reversible Door

Fully interchangeable left or right opening

White or black laminate wood worktop W: 20" x L: 12" Installed at an optimum height of 40"

Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Occupancy lights Height Adjustable Worktop



*Air Flow Diagram







