



Kubebooth Technical Data Sheet - KSelf*i* Floorless



Power Cord 10ft cord 120V/15Amp

Wall Construction Galvanized steel frames Sound insulation in all cavities

Door Lock Patch fit low noise- silent latch

Finishes TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Easy to Install Plug 8

Size Overall - W: 44" - D: 37" - H: 88"

Inside - W: 36" - D: 36" - H: 84" Weight

750 lbs/340 kg

Glass

10mm clear tempered Door - H: 88" x W: 32" Rear Panel - H: 88" x W: 44" Front Side Panel - H: 88" x W: 12"

Plug & Play

Acoustics Class A noise reduction

Air Exchange 100 complete air changes per hour

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan) Light 12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Reversible Door

Fully interchangeable left or right opening

Worktop

White or Black laminate wood worktop W: 20" x L: 12" Installed at an optimum height of 40"

Felt


Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit

Occupancy lights

Note: For your safety and optimal performance, this phone booth must be securely drilled to the floor during installation.



*Air Flow Diagram