







ISO 14001:2015 CERTIFIED COMPANY



Easy to Install





Kubebooth Technical Data Sheet - Kteam 4

Extendable



Overall - W: 88" - D: 73" - H: 88" Inside - W: 80" - D: 72" - H: 80"

Weight

1800 lbs/816 kg

Glass

10mm clear tempered Ceramic painted borders Door - H: 88" x W: 36" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 26"

Acoustics

NIC rating of 36 dB certified Noise cancellation technology

Moveable

Air Exchange

100 complete air changes per hour

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex Outlets

Motion detector (controls light & fan)

Mobility Kit

Includes casters with fasteners

Plug & Play

Light

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord

10ft cord 120V/15Amp

Wall Construction

Galvanized steel frames Sound insulation in all cavities

Finishes

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal Solution dyed polypropylene 28 oz, 10 gauge GreenGuard certified GLP8472 <450 NBS smoke

Substructure-rated MDF on unitized steel base.

Reversible Door

Fully interchangeable left or right opening

Worktop


White or Black laminate wood worktop D Shape L: 45" x W: 24" Installed at an optimum height of 28"

Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Smart lock Occupancy lights

65" Sofa (Customization available)



*Air Flow Diagram









