











Kubebooth Technical Data Sheet - Kteam 8

Size

Easy to Install

Moveable

Plug & Play

Overall - W: 88" - D: 145" - H: 88" Inside - W: 80" - D: 144" - H: 80"

Weight 3000 lbs/1361 kg

Glass 10mm clear tempered Ceramic painted borders Door - H: 88" x W: 36" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 26"

Acoustics

NIC rating of 36 dB certified Noise cancellation technology

Air Exchange

100 complete air changes per hour

Light

Mobility Kit

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Includes casters with fasteners

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation Power Cord 10ft cord 120V/15Amp

Wall Construction

Galvanized steel frames Sound insulation in all cavities

Finishes

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal Solution dyed polypropylene 28 oz, 10 gauge GreenGuard certified GLP8472 <450 NBS smoke

Reversible Door Fully interchangeable left

or right opening

Worktop

White or Black laminate wood worktop

O Shape

Felt


Interior sound absorption panels 60% recyclable

Options

Seismic bracing
One touch LCD control panel
LCD TV mount bracing
White glass board - W: 34" x L: 30"
Personalized company branding
Ethernet ports
Bluetooth speaker
Frosted film glass
External fire extinguisher unit
Smart lock
Occupancy lights







*Air Flow Diagram



Substructure-rated MDF on unitized steel base.







