





ISO 14001:2015 CERTIFIED COMPANY







Kubebooth Technical Data Sheet - Kteam 8

Weight

3000 lbs/1361 kg

Easy to Install

Moveable

Overall - W: 88" - D: 145" - H: 88"

Inside - W: 80" - D: 144" - H: 80"

Glass 10mm clear tempered

Rear Panels - H: 88" x W: 44"

Front Side Panels - H: 88" x W: 26"

Ceramic painted borders

Door - H: 88" x W: 36"

Acoustics

NIC rating of 36 dB certified Noise cancellation technology

Plug & Play

Air Exchange

100 complete air changes per hour

Mobility Kit

Includes casters with fasteners

Light


12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation Power Cord 10ft cord 120V/15Amp



Wall Construction

Galvanized steel frames Sound insulation in all cavities

Finishes

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal Solution dyed polypropylene 28 oz, 10 gauge GreenGuard certified GLP8472 <450 NBS smoke

Floor Ceiling

Substructure-rated MDF on unitized steel base.

Reversible Door Fully interchangeable left

or right opening

Worktop


White or Black laminate wood worktop D Shape

Felt

Interior sound absorption panels 60% recyclable

Options

Seismic bracing
One touch LCD control panel
LCD TV mount bracing
White glass board - W: 34" x L: 30"
Personalized company branding
Ethernet ports
Bluetooth speaker
Frosted film glass
External fire extinguisher unit
Smart lock
Occupancy lights



*Air Flow Diagram







