



# Kubebooth Technical Data Sheet - Kteam 4 Floorless

### Extendable

### Easy to Install

**Size** Overall - W: 88" - D: 73" - H: 88" Inside - W: 80" - D: 72" - H: 84"

Weight 1600 lbs/726 kg

### Glass

10mm clear tempered Door - H: 88" x W: 36" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 26"

**Reversible Door** Fully interchangeable left or right opening

#### Worktop

White or Black Laminate wood D shape worktop L: 45" x W: 24" Installed at an optimum height of 28"

#### Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Door lock Occupancy lights



## **Plug & Play**

Acoustics Class A noise reduction

Air Exchange 100 complete air changes per hour

Data Center UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan) Light 12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

#### Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord 10ft cord 120V/15Amp

Wall Construction Galvanized steel frames Sound insulation in all cavities Finishes

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Felt Interior sound absorption panels 60% recyclable

**Door Lock** Patch fit low noise- silent latch \*Air Flow Diagram

Note: This collaborative pod requires drilling to the floor during installation to ensure stability and safety for multiple users.