
















# **Kubebooth Technical Data Sheet - Kwe**

## **Extendable**



## Size Overall - W: 88" - D: 37" - H: 88" Inside - W: 80" - D: 36" - H:

### Weight

80"

1200 lbs/544 kg

10mm clear tempered

### Glass

Ceramic painted borders Door - H: 88" x W: 32" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 28"

## Easy to Install

### **Acoustics**

NIC rating of 36 dB certified Noise cancellation technology

Moveable

### Air Exchange

100 complete air changes per hour

### **Data Center**

**UL** approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

# Plug & Play

### **Mobility Kit**

Includes casters with fasteners

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

### Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation **Power Cord** 10ft cord 120V/15Amp

### Wall Construction

Galvanized steel frames Sound insulation in all cavities

### **Finishes**

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

### Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal Solution dyed polypropylene 28 oz, 10 gauge GreenGuard certified GLP8472 <450 NBS smoke

### Floor Ceiling

Substructure-rated MDF on unitized steel base.

### **Reversible Door**

Fully interchangeable left or right opening


### Worktop

White or Black laminate wood worktop D shape L: 24" x W:24" Installed at an optimum height of 28"

Interior sound absorption panels 60% recyclable

### **Options**

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W. 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Smart lock Occupancy lights



\*Air Flow Diagram







