















Kubebooth Technical Data Sheet - Kwe Floorless

Extendable

Easy to Install

Size Overall - W: 88" - D: 37" - H: 88" Inside - W: 80" - D: 36" - H: 84" Weight

1100 lbs/500 kg



10mm clear tempered Door - H: 88" x W: 32" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 28" Acoustics Class A noise reduction

Air Exchange 100 complete air changes per hour

Data Center UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

Light

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler Pre-engineered knockout hole for 3rd party sprinkler installation **Power Cord** 10ft cord 120V/15Amp



Door Lock

Patch fit low noise-silent latch

Wall Construction

Galvanized steel frames Sound insulation in all cavities

Finishes

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Reversible Door


Fully interchangeable left or right opening Worktop

White or Black laminate wood worktop D shape L: 24" x W:24" Installed at an optimum height of 28"

Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Door lock Occupancy lights



*Air Flow Diagram

Note: This meeting pod must be drilled to the floor to maintain structural integrity and ensure user safety.







