



Kubebooth Technical Data Sheet - Kwe Floorless

Extendable

Easy to Install

Size

Overall - W: 88" - D: 37" - H: 88" Inside - W: 80" - D: 36" - H: 84"

Weight 1100 lbs/500 kg

Glass

10mm clear tempered Door - H: 88" x W: 36" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 26"

Reversible Door

Fully interchangeable left or right opening Worktop White or Black laminate wood worktop D shape L: 24" x W:24" Installed at an optimum height of 28"

Acoustics Class A noise reduction

UL approved 1 USB A port,

100 complete air changes per hour

Air Exchange

Data Center

1 USB C port

2 Simplex outlets

Motion detector (controls light & fan)


Felt

Interior sound absorption panels 60% recyclable **Options** Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Door lock Occupancy lights




Light 12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler Pre-engineered knockout hole for 3rd party sprinkler installation Power Cord 10ft cord 120V/15Amp



*Air Flow Diagram

Note: This meeting pod must be drilled to the floor to maintain structural integrity and ensure user safety.



Door Lock Patch fit low noise- silent latch

Wall Construction Galvanized steel frames Sound insulation in all cavities

Finishes

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted